

DAYLIGHT

ESSENTIAL LED FLOODLIGHT

SURGE PROTECTION

UP TO 2KV

INFORMATION:

- Die Cast Aluminium Body
- Toughened Tempered Glass
- Large Voltage Operating Range 185v – 265v
- Operating Temperature -20° - +50°



EFFICIENCY
85lm/w



Ra (CRI)
>70



PF
>0.9



VOLTAGE
185-265
50/60Hz



ANGLE
120°



KELVIN TEMP
6500K
(daylight)

SHARED SPECS

PORT ELIZABETH
T: +27 41 484 3330

CAPE TOWN
T: +27 21 551 2400

DURBAN
T: +27 31 700 0055

JOHANNESBURG
T: +27 31 700 0055

BLOEMFONTEIN
T: +27 51 447 0020

HEAD OFFICE: Corner Darling & Delson Street, North End, Port Elizabeth, South Africa

www.daylight.co.za

*See product warranty terms and conditions at <https://daylight.co.za/warranty-terms-and-conditions/>

DAYLIGHT

LED FLOODLIGHT

PRODUCT	PRODUCT CODE	POWER	IP	LUMENS	FITTING SIZE	SURGE PROTECTION
	DLFL101	10W	65	850lm	96*90*25mm	2Kv
	DLFL102	20W	65	1700lm	116*106*25mm	2Kv
	DLFL103	30W	65	2550lm	143*125*25mm	2Kv
	DLFL104	50W	65	4250lm	177*152*25mm	2Kv
	DLFL105	100W	65	8500lm	253*225*29mm	2Kv
	DLFL106	150W	65	12750LM	320*282*30mm	2Kv
	DLFL107	200W	65	17000lm	375*310*30mm	2Kv

SHARED SPECS



EFFICIENCY
85lm/w



Ra (CRI)
>70



PF
>0.9



VOLTAGE
185-265
50/60Hz



ANGLE
120°



KELVIN TEMP
6500K
(daylight)

PORT ELIZABETH
T: +27 41 484 3330

CAPE TOWN
T: +27 21 551 2400

DURBAN
T: +27 31 700 0055

JOHANNESBURG
T: +27 31 700 0055

BLOEMFONTEIN
T: +27 51 447 0020

HEAD OFFICE: Corner Darling & Delson Street, North End, Port Elizabeth, South Africa

www.daylight.co.za

*See product warranty terms and conditions at <https://daylight.co.za/warranty-terms-and-conditions/>