Arco ELECTRONICS
Serving the Electronics Industry for More than 50 Years!
PRODUCT LINE
DISTRIBUTORS
PRESS RELEASES
RoHS STATEMENT
REQUEST FOR QUOTE
TOLL-FREE SALES: (800) 441-2726
SITE MAP CONTACT HOME

DM15 Series Mica Spec Details

Dipped Mica Capacitors **DM15 TYPE**

500VDC

Cap. Pf.	DM15 Style	MIL STYLE CM05	MAX DIM. L in. (mm)	W in. (mm)	T in. (mm)
1	010D	CD010D03	.450 (11.4)	.360 (9.1)	.170 (4.3)
2	020D		.450 (11.4)	.360 (9.1)	.170 (4.3)
3	030D		.450 (11.4)	.360 (9.1)	.170 (4.3)
4	040D		.450 (11.4)	.360 (9.1)	.170 (4.3)
5	050D	CD050D03	.450 (11.4)	.360 (9.1)	.170 (4.3)
6	060D	CD060D03	.450 (11.4)	.360 (9.1)	.170 (4.3)
7	070D	CD070D03	.450 (11.4)	.360 (9.1)	.170 (4.3)
8	080D	CD080D03	.450 (11.4)	.360 (9.1)	.170 (4.3)
10	100(J,D)	CD100D03	.450 (11.4)	.360 (9.1)	.170 (4.3)
12	120(J,D)	CD150J03	.450 (11.4)	.360 (9.1)	.170 (4.3)
15	150(J,D)	CD180J03	.450 (11.4)	.360 (9.1)	.170 (4.3)
18	180(J,D)	ED180J03	.450 (11.4)	.360 (9.1)	.170 (4.3)
20	200(J,D)	ED200J03	.450 (11.4)	.360 (9.1)	.170 (4.3)
22	220(J,D)	ED220J03	.450 (11.4)	.360 (9.1)	.170 (4.3)
24	240(J,D)	ED240J03	.450 (11.4)	.360 (9.1)	.170 (4.3)
27	270(J,G)	ED270(J,G)03	.450 (11.4)	.360 (9.1)	.170 (4.3)
30	300(J,G)	ED300(J,G)03	.450 (11.4)	.360 (9.1)	.170 (4.3)
33	330(J,G)	ED330(J,G)03	.450 (11.4)	.360 (9.1)	.170 (4.3)
36	360(J,G)	ED360(J,G)03	.450 (11.4)	.360 (9.1)	.170 (4.3)
39	390(J,G)	ED390(J,G)03	.450 (11.4)	.360 (9.1)	.170 (4.3)
43	430(J,G)	ED430(J,G)03	.450 (11.4)	.360 (9.1)	.170 (4.3)
47	470(J,G)	ED470(J,G)03	.450 (11.4)	.360 (9.1)	.170 (4.3)
50	500(J,G,F)		.450 (11.4)	.360 (9.1)	.170 (4.3)
51	510(J,G,F)	ED510(J,G,F)03	.450 (11.4)	.360 (9.1)	.170 (4.3)
56	560(J,G,F)	ED560(J,G,F)03	.450 (11.4)	.360 (9.1)	.170 (4.3)
62	620(J,G,F)	ED620(J,G,F)03	.450 (11.4)	.360 (9.1)	.170 (4.3)
68	680(J,G,F)	ED680(J,G,F)03	.450 (11.4)	.360 (9.1)	.180 (4.5)
75	750(J,G,F)	ED750(J,G,F)03	.450 (11.4)	.360 (9.1)	.180 (4.5)
82	820(J,G,F)	ED820(J,G,F)03	.450 (11.4)	.360 (9.1)	.180 (4.5)
91	910(J,G,F)	FD910(J,G,F)03	.460 (11.6)	.360 (9.1)	.180 (4.5)

Downloaded from Arrow.com.

100	101(J,G,F)	FD101(J,G,F)03	.460 (11.6)	.360 (9.1)	.180 (4.5)
110	111(J,G,F)	FD111(J,G,F)03	.460 (11.6)	.370 (9.4)	.180 (4.5)
120	121(J,G,F)	FD121(J,G,F)03	.460 (11.6)	.370 (9.4)	.180 (4.5)
130	131(J,G,F)	FD131(J,G,F)03	.460 (11.6)	.370 (9.4)	.180 (4.5)
150	151(J,G,F)	FD151(J,G,F)03	.460 (11.6)	.370 (9.4)	.190 (4.8)
160	161(J,G,F)	FD161(J,G,F)03	.460 (11.6)	.370 (9.4)	.190 (4.8)
180	181(J,G,F)	FD181(J,G,F)03	.460 (11.6)	.370 (9.4)	.190 (4.8)
200	201(J,G,F)	FD201(J,G,F)03	.460 (11.6)	.380 (9.6)	.190 (4.8)
220	221(J,G,F)	FD221(J,G,F)03	.460 (11.6)	.380 (9.6)	.200 (5.0)
240	241(J,G,F)	FD241(J,G,F)03	.460 (11.6)	.380 (9.6)	.200 (5.0)
250	251(J,G,F)		.460 (11.6)	.380 (9.6)	.200 (5.0)
270	271(J,G,F)	FD271)J,G,F)03	.470 (11.9)	.390 (9.9)	.210 (5.3)
300	301(J,G,F)	FD301(J,G,F)03	.470 (11.9)	.390 (9.9)	.210 (5.3)
330	331(J,G,F)	FD331(J,G,F)03	.470 (11.9)	.390 (9.9)	.210 (5.3)
360	361(J,G,F)	FD361(J,G,F)03	.470 (11.9)	.390 (9.9)	.210 (5.3)
390	391(J,G,F)	FD391(J,G,F)03	.470 (11.9)	.390 (9.9)	.210 (5.3)
430	431(J,G,F)		.470 (11.9)	.390 (9.9)	.210 (5.3)
470	471(J,G,F)		.470 (11.9)	.400 (10.1)	.220 (5.5)
500	501(J,G,F)		.470 (11.9)	.400 (10.1)	.220 (5.5)
510	511(J,G,F)		.470 (11.9)	.400 (10.1)	.220 (5.5)
560	561(J,G,F)500V		.480 (12.1)	.410 (10.4)	.230 (5.5)
620	621(J,G,F)500V		.480 (12.1)	.410 (10.4)	.230 (5.5)
680	681(J,G,F)500V		.490 (12.4)	.420 (10.6)	.240 (6.0)
750	751(J,G,F)500V		.500 (12.7)	.430 (10.9)	.250 (6.3)

300VDC

				MAX DIM.	
Cap.	**DM15**	**MIL STYLE**	**L**	**W**	**T**
Pf.	**Style**	**CM05**	**in. (mm)**	**in. (mm)**	**in. (mm)**
300	301(J,G,F)		.460 (11.6)	.380 (9.6)	.200 (5.0)
330	331(J,G,F)		.460 (11.6)	.380 (9.6)	.200 (5.0)
360	361(J,G,F)		.460 (11.6)	.380 (9.6)	.200 (5.0)
390	391(J,G,F)		.460 (11.6)	.380 (9.6)	.200 (5.0)
430	431(J,G,F)		.460 (11.6)	.380 (9.6)	.200 (5.0)
470	471(J,G,F)		.460 (11.6)	.380 (9.6)	.200 (5.0)
500	501(J,G,F)		.460 (11.6)	.380 (9.6)	.200 (5.0)
510	511(J,G,F)		.460 (11.6)	.380 (9.6)	.200 (5.0)
560	561(J,G,F)		.460 (11.6)	.380 (9.6)	.200 (5.0)
620	621(J,G,F)		.470 (11.9)	.390 (9.9)	.210 (5.3)
680	681(J,G,F)		.470 (11.9)	.390 (9.9)	.210 (5.3)
750	751(J,G,F)		.470 (11.9)	.390 (9.9)	.210 (5.3)
820	821(J,G,F)		.470 (11.9)	.390 (9.9)	.210 (5.3)
910	911(J,G,F)		.470 (11.9)	.400 (10.1)	.210 (5.3)
1000	102(J,G,F)		.480 (12.1)	.400 (10.1)	.220 (5.5)
1100	112(J,G,F)		.490 (12.4)	.420 (10.6)	.230 (5.8)
1200	122(J,G,F)		.500 (12.7)	.430 (10.9)	.250 (6.3)

100VDC

MAX DIM.

Downloaded from Arrow.com.

Cap. Pf.	DM15 Style	MIL STYLE CM05	L in. (mm)	W in. (mm)	T in. (mm)
910	911(J,G,F)		.470 (11.9)	.400 (10.1)	.220 (5.5)
1000	102(J,G,F)		.480 (12.1)	.400 (10.1)	.230 (5.8)
1100	112(J,G,F)		.480 (12.1)	.400 (10.1)	.230 (5.8)
1200	122(J,G,F)		.490 (12.4)	.420 (10.6)	.240 (6.0)
1300	132(J,G,F)		.500 (12.7)	.430 (10.9)	.250 (6.3)
1500	152(J,G,F)		.500 (12.7)	.430 (10.9)	.250 (6.3)
1600	162(J,G,F)		.500 (12.7)	.430 (10.9)	.250 (6.3)

50VDC

Cap. Pf.	DM15 Style	MIL STYLE CM05	L in. (mm)	MAX DIM. W in. (mm)	T in. (mm)
1800	182(J,G,F)		.480 (12.1)	.400 (10.1)	.230 (5.8)
2000	202(J,G,F)		.490 (12.4)	.420 (10.6)	.240 (6.0)

Copyright 2005 Arco Electronics Inc., All Rights Reserved

Downloaded from Arrow.com.